

ColorFill

Product Description

ColorFill is a sealant with a characteristic solvent smell. It comes in a variety of colors.

Benefits

- ColorFill is easy to apply, dries quickly and is impervious to water when dry.
- Good heat resistance to 284°F (140°C).
- Color is permanent and is UV resistant.
- ColorFill has a shelf life of 2 year in unopened packaging.

Applications

ColorFill is used as a sealant for countertop miter joints, as a repair compound for damage in laminate surfaces and as a gap-filling sealant for laminate flooring installations.

A 25g tube is sufficient for a 25.5" (650mm) countertop.

Directions of Use

For repairs: apply from tube and smooth with spatula.

For mitres: a bead of ColorFill is applied around the miter before the edges are brought together and the joining bolts fastened.

Clean any excess product with acetone, taking care not to remove any from the repair/joint.

Surface Preparations and Finishing

- Application temperature 41°F to 86°F (5°C to +30°C) —environment and substrate.
- Surfaces must be dry, clean and solid.

Cleaning

Clean with acetone solvent.

Additional information

Viscosity	45000 cP
Cure Speed	Air drying — 0.04in(1mm)/30min
Skin Forming	Touch dry after 2min
Shrink	~30%
Gap Fill	3/4" (20mm)
% Volatile	50% (+/- 5%)
Flash Point	<32°F (0°C)
Shelf Life	2 years @ 68°F(20°C)
Specific Gravity	~0.96
Operating Temperature	14°F to 86°F (-10°C to +30°C)

Color(s)

Various

Shelf Life

In unopened original packaging between +41°F and 77°F (5°C and 25°C), shelf-life till 24 months after production date, stored in a dry place.

Health & Safety

- Keep in a cool well-ventilated area away from sources of ignition.
- Keep away from children at all times.
- Keep containers sealed.
- Use in a well-ventilated area.
- Avoid contact with skin and eyes

For further information, please read the product SDS.

Note: The data, information and values contained in this Technical Data Sheet have been obtained by conducting various tests in a controlled laboratory environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. IPS Adhesives Inc. cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warranties or implied usage obligations should not be attributed to and are not the responsibility of IPS Adhesives Inc. IPS Adhesives Inc. are not liable for any financial loss or other damages incurred by the user as a result of the use of this product.